



Developing Infrastructure and Operating Models for Intermodal Shift

Best practices for the management of combined transport terminals (Workpackage A4)

February 2007





ISBN 2-7461-1308-2 Warning No part of this publication may be copied, reproduced or distributed by any means whatsoever, including electronic, except for private and individual use, without the express permission of the International Union of Railways (UIC). The same applies for translation, adaptation or transformation, arrangement or reproduction

by any method or procedure whatsoever. The sole exceptions - noting the author's name and the source - are "analyses and brief quotations justified by the critical, argumentative, educational, scientific or informative nature of

the publication into which they are incorporated".

© Copyright - Paris, 2007

(Articles L 122-4 and L122-5 of the French Intellectual Property Code).

Contents

1	Objectives and methodology	1
2	Impact of combined transport evolution on terminal capacity	4
3	Determinants of combined transport terminal capacity	9
4	Best practices in terminal capacity management	12
	4.1 - Increase of flow factor	13
	4.2 - Control of shunting services	15
	4.3 - Supply of road trucking services	17
	4.4 - Extension of terminal opening time	18
	4.5 - Bonus-malus incentives for the use of interim storage space	20
	4.6 - IT-based capacity management systems	23
	4.7 - Automated loading unit identification	26
	4.8 - Separation of rail-side and road-side handlings	29
	4.9 - Task management according to pre-notification	31
	4.10 - Punctual rail services	32
5	Conclusions and recommendations	34
6	Workshop participants	37
List of Figures		39