

# UIRR 2026

Map of the codified lines for Swap Bodies

Legend:

Width	Width
≤ 2550mm	>2550 ≤ 2600mm
C 22	C 341
C 32	C 351
C 45	C 364
C 70	C 400
C 80	C 400
C 80	C 410
	see remarks (directly on the route or as additional text box)

The admissible edge heights (cm) of the loading units carried on the wagons are calculated as follows:

C?? Codification number added by the number '245' (example: C 22 = 22+245 = 267 cm)

C?? Codification number reduced by the number '85' (example: C 341 = 341-85 = 256 cm)

For more information on terminals refer to the Rail Facilities Portal <https://railfacilitiesportal.eu>


- Transshipment facility / terminal
  - Cities
- Copyright by UIRR - 2026



For the UK traffic through the Channel the mentioned codifications are only valid for loaded swap bodies:

Wagon	Lignes	Width (mm)		
		2500	2550	2600
	a	S 18 (S21)*	S 18 (S21)*	-
	b	S 32	S 30	S 360
	c	S 32	-	-
	a	S 30 (S34)*	S 21 (S25)*	-
	b	S 44	S 42	-
	c	S 44	-	-

\* only with flat roof



The UIRR maintains this codification map to enhance public access to information related to Combined Transport. UIRR accepts no responsibility or liability whatsoever with regard to the information contained in this document.

The railway profiles might be higher than those indicated in the map upon verification by the infrastructure manager and authorisation for an exceptional transport.

Some CT profiles are extracted from the RINF and CIP database.